

FILTERING HALF MASK



Colors:

Sizes:

Packing:

Package:

UNI

10/120 (PC.)

5 KG / (47X42X31CM)

Dust half mask with valve.

- type FFP3: protects the respiratory system against solid and liquid aerosols, as long as the concentration of the dispersed phase of these aerosols does not exceed 20 x WEL
- worn with adjustable elastic bands
- exhaust valve located at the front
- foam seal around the entire rim of the half mask
- the conical shape of the mask, additionally profiled to the face, allows for adjustment
- does not contain metal elements
- perfect protection against metallic dust and smoke, particles and mists of various agents
- used in wood and metal processing, grinding and painting (also with paints containing lead chromate)
- half mask with anti-smog properties
- placed in a box that allows for convenient presentation at the exhibition
- small package of 10 pcs.
- compliant with the EN149 standard

EAN CODES:

UNI

5902973661378

RECOMMENDED:



FEATURES:

FFP3 FFP3 type mask

respiration valve

RECOMMENDED FOR:

- Metalworking as well as operators of machinery and equipment and their repair
- Construction and renovation works/ Assembly and installation works/ Construction of roads
- Automotive industry including construction, mechanics and repair of vehicles as well as varnishing
- Extractive industry including mining
- Agriculture/ Horticulture/ Forestry/ Hunting/ Fishing
- Craft including production and processing of glass, ceramics, wood and printing houses

STANDARDS:

